

[54] **INFORMATION PROCESSOR HAVING INFORMATION CORRECTING FUNCTION**

- [75] Inventor: **Tetsuji Oguchi**, Tokyo, Japan
- [73] Assignee: **Nippon Electric Co., Ltd.**, Tokyo, Japan
- [21] Appl. No.: **529,921**
- [22] Filed: **Sep. 6, 1983**

Related U.S. Application Data

- [63] Continuation of Ser. No. 206,061, Nov. 12, 1980, abandoned.

[30] **Foreign Application Priority Data**

- Nov. 15, 1979 [JP] Japan 54-148031
- [51] Int. Cl.⁴ **G06F 13/00**
- [52] U.S. Cl. **364/200**
- [58] Field of Search 364/200, 900; 340/703, 340/717, 709, 723

References Cited

U.S. PATENT DOCUMENTS

2,552,629	5/1951	Hamming	371/37
3,402,390	9/1968	Tsimbidis	371/37
4,016,544	4/1977	Morita et al.	340/703
4,149,184	4/1979	Giddings et al.	340/703
4,203,102	5/1980	Hydes	340/723
4,290,063	9/1981	Traster	340/723

4,296,494 10/1981 Ishikawa et al. 371/13

OTHER PUBLICATIONS

Bell System Technical Journal, R. W. Hamming, Apr. 1950, pp. 147-160.

Primary Examiner—Thomas M. Heckler
Attorney, Agent, or Firm—Laff, Whitesel, Conte & Saret

[57] **ABSTRACT**

The invention selectively designates a specific portion of information which is stored in a memory to identify information which is to be corrected. It further enables a correction of only the suitably designated portion. The read out of information having the corrected information is set in a state which is ready for use. Accordingly, it is not necessary to use a bit addressing circuit, as used in the prior art, this simplifying both the circuit design and the wiring. It is also possible to designate more than one arbitrary item of information as portions which are to be corrected and then to correct all designated information simultaneously. Thus, the read out information is corrected at a high speed. In addition, the number of information items which are capable of correction is not limited by unnecessary bit addressing. This enables an increase in the number of memory elements, and makes the system quite useful as a control device for CRT display systems.

8 Claims, 12 Drawing Figures

